

SLIDING DOOR FITTINGS - FLUSH 125Kgs

Special Features

- Precision roller system has good load bearing and life.
- Special guides and catches to secure the door.
- Special flush fittings to conceal gaps.
- Load capability - 125 kgs.

Specifications

Item	Code Nos.	Max. Load Kgs.	Length	Finish
Sliding Fitting	SDF-125FM	125	-	ZW
Aluminium Section (125 Kgs.)	SDF-AS-125M-2	-	2.44 mtrs	AS
	SDF-AS-125M-3	-	3.66 mtrs	AS
Track for Sliding Door Fitting with Fixed Glass	SDF-125-ATG-2	-	2.44 mtrs	AS
	SDF-125-ATG-3	-	3.66 mtrs	AS
Wall Mounting Bracket	SDF-WB	-	-	ZW



Fitting Instructions

1. Flush model is provided with channels (2 nos.) which are concealed in grooves 21 x 21mm at the top of the door to have minimum gap (Refer Fig. 1).
2. By removing the flush cover in the channel the inner bracket slides out into which the M8 bolts and nuts are fastened. After adjusting the height the cover is replaced (Refer Fig 1).
3. The bottom guides (2 nos.) are fitted on the floor. The groove required in the door is 9mm wide and 12mm deep (Refer Fig. 2).
4. The catch (2 nos) is fitted in the aluminum section at both ends and can be adjusted for pressure (Refer Fig. 3).
5. Optional wall mounting brackets are available. This is to be fitted every 600mm on aluminum section (Refer Fig. 4).

