

# CUPBOARD LATCH

Design Reg. Nos: 56st: 166020/93 /  
56cr: 166803/94 / 150st: 166933/94



## Special Features

- Spring loaded for safety and smooth operations.
- Cranked bolt with plate for internal fitting with external shutter.
- Straight bolt with clip for external fitting with flush shutter.
- Also, straight bolt with plate for internal fitting with recessed shutter.

## Specifications

Model	Code Nos.	Internal Cabinet Height(mm)	Shutter Type	For Engaging	Finish
Straight Bolt 56 mm	LS-56	370 to 500	Recessed (Inset)	Clip	ZW/ ZB
Cranked Bolt 56 mm	LC-56	460 to 580	External (Overlay)	Plate	
Straight Bolt 96 mm	LS-96	530 to 700	Recessed (Inset)	Clip	
Cranked Bolt 96 mm	LC-96	530 to 700	External (Overlay)	Plate	
Straight Bolt 150 mm	LS-150	530 to 700	Recessed (Inset)	Clip	
Cranked Bolt 150 mm	LC-150	530 to 700	External (Overlay)	Plate	
Straight Bolt 56 mm (SS 304)	LS-56-SS	370 to 500	Recessed (Inset)	Clip	SS 304
Cranked Bolt 56 mm (SS 304)	LC-56-SS	460 to 580	External (Overlay)	Plate	
Straight Bolt 96 mm (SS 304)	LS-96-SS	530 to 700	Recessed (Inset)	Clip	
Cranked Bolt 96 mm (SS 304)	LC-96-SS	530 to 700	External (Overlay)	Plate	
Straight Bolt 150 mm (SS 304)	LS-150-SS	530 to 700	Recessed (Inset)	Clip	
Cranked Bolt 150 mm (SS 304)	LC-150-SS	530 to 700	External (Overlay)	Plate	



Latch - Cranked (ZW)



Latch - Cranked (BL)



Latch - Straight (ZW)



Latch - Straight (BL)

Model	A	B	C
Straight Bolt 56 mm	56.0	3.0	8.0
Cranked Bolt 56 mm		13.0	8.0
Straight Bolt 96 mm	96.0	0	10.0
Cranked Bolt 96 mm		13.0	10.0
Straight Bolt 150 mm	150.0	0	12.0
Cranked Bolt 150 mm		13.0	12.0

### APPLICATION

