

TABLE BRACKET DAMPER

Special Features

- Make your folding table 'Soft-close' with this new Damper.
- Refer the appropriate recommendation of sizes of table tops and dampers as mentioned in specification table.
- Designed to be used with Ebco:
Table Brackets Regular: Code – TB30/40/50/60
Table Bracket Recessed: Code – TBR30/40/50
- Min. Table top thickness: 25mm (Table Bracket - Recessed) & 18mm (Table Bracket Regular)
- Finish: Anthracite



Specifications

| Code Nos. | Max. Table Top Size* (in mm) W x D x H | Finish |
|-----------|---|--------|
| TBD-7L | 600 x 600 x 25 | AT |
| TBD-25H | 1200 x 650 x 25 | |

* Approximate size considering MDF Ply

Fitting Instructions

1. Drill Ø5mm holes under the table top & onto wall and fit damper as per dimensions shown in Fig.1 for Table bracket & Fig. 2 for Table bracket Recessed.
2. For fitting Table Bracket Recessed additional routing to be done in table top as per dimensions shown in Fig.3
3. One must take care to remove any items from the table top before closing it.
4. Do not press and force the fittings to Fold as shown in Fig. 4.
5. The wall must be of solid wood, brick work or concrete only. Do not use on plywood, blockboard etc.

