PHIL RECESS CSK HEAD DRILL SCREW

Special Features

- Ideal to use in the manufacturing of Aluminium/UPVC windows, partitions, etc.
- High pull out resistance.
- Can be reused.
- Manufactured to international specifications and standards.
- Choice of diameter and lengths ensure proper selection for application.



Specifications

Item	Code Nos.	Size in mm	Finish
Phil Recess CSK Head Drill Screws	CDS-3913	3.9 x 13	ZW
	CDS-3916	3.9 x 16	
	CDS-3919	3.9 x 19	
	CDS-3925	3.9 x 25	
	CDS-3930	3.9 x 30	
	CDS-3938	3.9 x 38	
	CDS-3950	3.9 x 50	

Code Nos.	Size		D	d	A	H	P	Y	Z	Q
CDS-3913	3.9 x 13mm	Min.	3.73	2.73	7.14	Ref. 2.30	1.40	3.05	Ref. 4.50	2.03
		Max.	3.91	2.92	7.50			3.15		2.53
CDS-3916	3.9 x 16mm	Min.	3.73	2.73	7.14	Ref. 2.30	1.40	3.05	Ref. 4.50	2.03
		Max.	3.91	2.92	7.50			3.15		2.53
CDS-3919	3.9 x 19mm	Min.	3.73	2.73	7.14	Ref. 2.30	1.40	3.05	Ref. 4.50	2.03
		Max.	3.91	2.92	7.50			3.15		2.53
CDS-3925	3.9 x 25mm	Min.	3.73	2.73	7.14	Ref. 2.30	1.40	3.05	Ref. 4.50	2.03
		Max.	3.91	2.92	7.50			3.15		2.53
CDS-3938	3.9 x 38mm	Min.	3.73	2.73	7.14	Ref. 2.30	1.40	3.05	Ref. 4.50	2.03
		Max.	3.91	2.92	7.50			3.15		2.53

Material	C1022 Steel
Thread Type	3.9 - 1.4 x L
Case Hardness	Hv 550 Min.
Core Hardness	Hv 320 - 420
Torque : Min.	35 Kg-cm
Surface Finish	ZW

Length	13 mm	16 mm	19 mm	25 mm	38 mm
Tol. ±	0.80 mm	0.80 mm	1.00 mm	1.00 mm	1.00 mm

