

# POZI RECESS PAN HEAD CHIPBOARD SCREW

## Special Features

- Ideal furniture fastener, providing high pull out resistance.
- Can be reused.
- Manufactured to international specifications and standards.
- Choice of diameters and lengths ensure proper selection for application.



## Specifications

Item	Code Nos.	Size in mm	Finish
Pozi Recess Pan Head Chipboard Screw Hardened Zinc Plated	PCBS-3012	3 x 12 (5 x 12)	ZW
	PCBS-3016	3 x 16 (5 x 16)	
	PCBS-3512	3.5 x 12 (6 x 12)	
	PCBS-3516	3.5 x 16 (6 x 16)	
	PCBS-3520	3.5 x 20 (6 x 20)	
	PCBS-4016	4 X 16 (8 x 16)	
	PCBS-4025	4 X 25 (8 x 25)	
	PCBS-4030	4 X 30 (8 x 30)	
	PCBS-4035	4 x 35 (8 x 35)	
	PCBS-4040	4 X 40 (8 x 40)	

		Recess No.	1	2	2	2	2	3
Pozi Drive	m	Min.	3.12	3.81	4.65	5.00	5.28	6.63
	n	Min.	1.58	1.47	1.88	2.28	2.28	3.02
		Max.	1.85	1.93	2.34	2.74	2.74	3.48

Diameter		3	3.5	4
d1	Min.	2.75	3.20	3.70
	Max.	3.05	3.55	4.05
d2	Min.	1.50	1.80	2.15
	Max.	1.90	2.20	2.55
D	Min.	5.52	6.52	7.42
	Max.	6.00	7.00	8.00
p	±10%	1.35	1.60	1.80
K	Max.	2.17	2.22	2.69
	Max.	2.37	2.52	2.92

Breaking Torque	Min/Nm.	1.50	2.00	3.00	4.30	6.20	10.80
Bending Angle	Min.	15°	15°	15°	15°	15°	15°

Length	12	16	20	25	30	35	40
Tol. ±	0.90	0.90	1.06	1.06	1.06	1.25	1.25

Material	C-1022 Steel Heat treated Case Hardened
Surface Hardness	Min. 450 HV 0.3
Surface Finish	Zinc Plated with Blue & Yellow Passivation

Chipboard Screws - Pan Head

