
SLEEK TELESCOPIC DRAWER SLIDE - 35

Design Reg. No: 170523/96

Special Features

- Precision ball bearing.
- Full extension of drawer.
- Direct fitting from front.
- Removable drawer with Latch.
- System 32 Installation.
- Load capacity : 35 Kgs.




Specifications

Code Nos.	Length (mm)	Extension (mm)	Gap / Side (mm)	Max. Load (Kgs.)	Finish
STDS-35-35	350	350	12.7 to 13.0	35	ZW/ZB
STDS-40-35	400	400			
STDS-45-35	450	450			
STDS-50-35	500	500			

Fitting Instructions

1. To install Sleek Telescopic Drawer Slide, 12.7 to 13.0 mm gap per side is required between cabinet and drawer (Refer Fig. 1).
2. Depress latch and remove the Inner slide (Refer Fig. 2).
3. Fit Outer (Fixed) slide on to the inside of the cabinet, access to holes can be got through slots in Intermediate slide.
4. Slides should be fitted parallel and screws tightened fully to avoid gaps.
5. Fit Inner slide on to the outside of the drawer.
6. Now slide the drawer with inner slide fitted on to the Intermediate slides on the cabinet till the latch engages automatically.

DRILLING DIAGRAM FOR DRAWER






Fig. 1





Fig. 2

DRILLING DIAGRAM FOR CABINET



Caution

For efficiency and durability.

- Strictly maintain 12.7 to 13.0 mm side gap.
- Fit slides parallel and at equal heights.
- Do not apply paint or polish.
- Do not let saw dust enter into the slides.